

AMENDMENTS TO THE SPECIFICATION

Please replace the first paragraph on page 3 with the following:

$$B \geq \frac{1}{3} \times K + 0.5 \quad 0.5 \quad (1)$$

with $K = \text{Min}(I^*; J^*)$

$I^* = \text{Max}(0; I)$ and $J^* = \text{Max}(0; J)$

$I = \text{Min}(N; N - 0.29 \quad 0.29(Ti - 5))$

$J = \text{Min}\left(N; 0.5 \quad 0.5 \left(N - 0.52 \quad 0.52 Al + \sqrt{(N - 0.52 \quad 0.52 Al)^2 + 283}\right)\right),$

the contents of silicon and ~~aluminium~~ aluminum of the composition also complying with the following conditions:

if $C > 0.145$, then $Si + Al < 0.95$

and whose structure is bainitic, martensitic or martensitic-bainitic and also comprises from 3 to 20% of residual austenite, preferably from 5 to 20% of residual austenite.

Please replace the paragraph bridging pages 6 and 7 with the following:

- the contents of ~~aluminium~~ aluminum, boron, titanium and nitrogen, expressed in thousandths of %, of the composition also satisfying the following relationship

$$B \geq \frac{1}{3} \times K + 0.5 \quad 0.5 \quad (1)$$

with $K = \text{Min}(I^*; J^*)$

$I^* = \text{Max}(0; I)$ and $J^* = \text{Max}(0; J)$

$I = \text{Min}(N; N - 0.29 \quad 0.29(Ti - 5))$

$J = \text{Min}\left(N; 0.5 \quad 0.5 \left(N - 0.52 \quad 0.52 Al + \sqrt{(N - 0.52 \quad 0.52 Al)^2 + 283}\right)\right),$

with the additional condition that:

- if $C > 0.145$ (and preferably > 0.140), then $Si + Al < 0.95$, and preferably < 0.90 , in order clearly to delimit the invention with respect to the earlier application EP 0 725 156,